



Aputure LS 60d



Product Description

The Light Storm 60d is a daylight-balanced (5600K / D56) adjustable focusing LED light, which uses precision aspherical optics to internally adjust the spot/flood beam angle between 15°~45°.

The 60d can be powered using the included AC adapter or via weatherproof DC power connector with either the included Dual Sony-NP-F Battery Plate Adapter or a cinema battery with D-Tap output, such as a V-Mount Battery. All of these power solutions can be mounted onto the V-Mount receiver on the side of the LS 60d's yoke for fast and compact operation.

The LS 60d is also weatherproof (dust and water-resistant), making it built to withstand any filmmaking environment.

In addition to being a focusable LED fixture, complete with an 8-Leaf Barndoors, the LS 60d is compatible with Bowens Mount soft light modifiers via its included Bowens Mount adapter.

Uniquely, the LS 60 series lights can use the Aputure Spotlight Mini Zoom and LS 60 Softbox, which are both sold separately. The Spotlight Mini Zoom is a precision projection attachment for the LS 60d and 60x, which accepts M-Size Gobos, and has a unique 15°~30° variable beam angle. The LS 60 Softbox is a compact square softbox that can turn the 60d from a hard point-source to a soft light in seconds.

Main Features

- 15°~45° Adjustable Spot/Flood Beam Angle
- Up to 50,000 lux+ @ 1 meter in full spot (15°)
- Color Temperature: 5600K
- Weatherproof (Dust and Water Resistant)
- Use One NP-F Battery for Half Power; Two for Full Power
- D-Tap Battery Operable
- V-Mount Receiver on Yoke
- Sidus Link Mobile App Control
- Custom Bowens Mount Adapter
- Compatible "Spotlight Mini Zoom" Projection Lens & "LS 60 Softbox"

Photometrics

Distance		1m	3m	5m
Spot (15°)	Lux	50,000	7,000	2,500
	Fc	4,645	650	232
Flood (45°)	Lux	8,300	1,000	370
	Fc	771	92	34

What's in the Box

Name	Quantity
LS 60d Lamp Head	1
LS 60 8-Leaf Barndoors	1
Power Supply	1
AC IEC Power Cable	1
Dual Sony NP-F Battery Plate Adapter for LS 60	1
D-Tap Power Cable (4-Pin)	1
Bowens Mount to LS 60 Adapter	1
Carrying Case	1

More Pictures





Aputure LS 60d



Specifications

CCT	5600K	
CRI	95+	
TLCI	95+	
CQS	93	
SSI (D56)	72	
Beam Angle	15° ~ 45°	
Output Wattage	60W	
Max Power Draw	90W	
Operating Current	<6.5A (Max)	
Operating Voltage (Power Supply)	19V	
Operating Voltage (Battery)	Sony NP-F	6 ~ 8.4V (Single battery) 12 ~ 16.8V (Dual battery)
	D-Tap	12 ~ 16.8V
Operating Temperature	-20°C ~ 45°C / -4°F ~ 113°F	
Control Methods	On-board, Sidus Link (Sidus Mesh™)	
Wireless Operating Range (Bluetooth)	≤ 80m / 262.5ft	
Screen Type	OLED	
Weatherproofing	Yes	
Cooling Method	Active Cooling	
Cable Type	Head Cable	4-pin DC Twist Lock Cable
	Power Cable	Locking IEC Power Cable (4m)
Accessory Mount	LS 60 Mini Mount	
Accessory Mount Diameter	120mm / 4.72in	

Specifications

Weight	Lamp Head	1.8kg / 3.968lbs
	Barn Doors	222g / 0.489lbs
	Power Supply	370g / 0.816lbs
	NP-F Battery Plate	134g / 0.295lbs
	Total w/ Case	4.475kg / 9.866lbs
Dimensions	Lamp Head without Yoke	209*116mm / 8.23*4.57in
	Lamp Head with Yoke	280*156*127mm / 11.02*6.14*5in
	Barn Doors Closer	134*108*33mm / 5.28*4.25*1in
	Power Supply	135*56*34mm / 5.31*2.2*1in
	NP-F Battery Plate	103*87*25mm / 4.06*3.43*1in
	Case	420*200*200mm / 16.54*7.87*8in

Sales & Shipping Information

Product Name	Aputure LS 60d	
SKU	US Plug	ALS60DUS
	UK Plug	ALS60DUK
	EU Plug	ALS60DEU
	AU Plug	ALS60DAU
Product code EU	6971842181230	
Product code UK	6971842181360	
Battery	N/A	
Package Dimensions	430*205*240mm / 16.9*8.1*9.4in	
Net Weight	3185g / 7.02lbs	
Gross Weight	4865g / 10.73lbs	
Carton Quantity	3 pcs	
Carton Dimensions	670*470*280mm / 26.4*18.5*11in	
Carton Weight	15715g / 34.65lbs	